

Technical Product Information

www.usglobalpetroleum.com

www.everestoil.com

773-376-9660



dexos1™ GEN 2 License # D10384HG117

**Premium
Performance**

**API SN PLUS
ILSAC GF-5**

EVEREST®

Full Synthetic SAE 5W-30 Motor Oil

EVEREST dexos1™ GEN 2 Full Synthetic SAE 5W-30 Motor Oil is formulated from select low-friction, full synthetic base stocks and an advanced technology additive system licensed by General Motors to meet their Global Engine Oil Specification. It provides excellent oxidation stability, superior resistance to sludge formation and varnish deposits, reduces friction and wear at start-up and protects your engine even under the toughest driving conditions. EVEREST dexos1™ GEN 2 Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile and stationary engines.

EVEREST dexos1™ GEN 2 Full Synthetic SAE 5W-30 Motor Oil meets or exceeds stringent GM dexos1™ GEN 2 requirements, ILSAC GF-5 and American Petroleum Institute (API) Resource Conserving SN PLUS service classifications as well as all earlier API categories. EVEREST dexos1™ GEN 2 Full Synthetic SAE 5W-30 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA A1/B1 & A5/B5, Chrysler MS6395M, Ford WSS-M2C929A, WSS-M2C946A, GM 6094M, Porsche, Renault, and other OEM's specifications where a full synthetic API SN motor oil is recommended.

Benefits and Applications

- Maximum full synthetic dexos1® GEN 2 protection
- Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- Superior resistance to sludge and varnish deposit formation

5W-30 Typical Characteristics - V200114

SAE GRADE	dexos1™	5W-30
API SERVICE		SN PLUS/GF-5
API Gravity	ASTM D4052-11	35.62
Flash Point, COC °C/°F	ASTM D92	228 / 442.4
Pour Point, °C/°F	ASTM D97	-48 / -54.4
Viscosity @ 40°C, cSt	ASTM D445	61.12
Viscosity @ 100°C, cSt	ASTM D445	10.94
Viscosity Index	ASTM D2270	173
CCS, mPa-sec °C max	ASTM D5293	3730 @ -30
Total Base No. TBN	ASTM D2896	8.0

Typical test data are average values only.
Minor variations, which do not affect performance, may occur.

**API SN PLUS
ILSAC GF-5**

ACEA A1/B1 & A5/B5, GM
6094M, Chrysler MS6395M,
Ford WSS-M2C929A,
WSS-M2C946A,
Porsche, Renault



HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.