

TITLE: AW-46 Hydraulic Fluid

APPROVALS: ...

Field Tested: Cincinnati Fives P-68, P-69, P-70, Parker Hannifin HF-0, HF-1, HF-2, Vickers 35VQ25A, Eaton/Vickers M-2950-S, I-286-S, Ford M6C32, Chrysler, General Motors LS-2, DIN 51524 Part 1 and 2, ASTM D6158, ISO 11158

- Excellent thermal stability
- Special additives provide sludge and deposit control, and longer service life
- Excellent rust and corrosion protection for all system components
- Provide superior water separation and demulsibility
- Excellent anti-foam protection and rapid air release
- Provides anti-wear protection for pumps, motors, valves and other hydraulic circuit components operating under high pressures and loads

Everest AW-46 Anti-Wear Hydraulic Oil is a premium quality general purpose anti-wear hydraulic fluid containing a zinc/phosphorous additive to minimize wear and provides superior thermal stability, anti-foam, rust, corrosion and oxidation protection in high-speed, high-pressure vane, gear, and piston pumps operating over a wide temperature range. It is formulated according to the ISO viscosity grade classifications to perform in extended service intervals to reduce downtime and increase time between equipment service. Everest Anti-Wear Hydraulic Oil meets, exceeds, or match the performance specifications and complies with most industrial, marine and mobile applications where service requirements are normal to moderate and long-term, heavy-duty wear protection is not critical including: Cincinnati Fives P-68, P-69, P-70, Parker Hannifin HF-0, HF-1, HF-2, Vickers 35VQ25A, Eaton/Vickers M-2950-S, I-286-S, Ford M6C32, Chrysler, General Motors LS-2, DIN 51524 Part 1 and 2, ASTM D6158, ISO 11158 and US Steel 136 specifications for stability and durability.

SIZE:	PART NUMBER:	BAR CODE:
QUART	-	-
GALLON	-	-
5-QUART	-	-
5 GAL	FPAW460EV05GHF	816752011689
16GAL KEG	FPAW460EV16KHF	816752012310
55 GAL	FPAW460EV055HF	816752011696
1-Liter	-	-
4-Liter	-	-
5-Liter	-	-